

Electro actuators with ball valves



PARAMETERS

- outlet moment 34 to 598 Nm (acc. to version)
- complies with IEC IP67
- each unit has two STOP switches
- polycarbon cover, aluminium base with surface treatment
- position indicators
- manual control
- version: 230 VAC, 24 VDC , 24 VDC, 12 VDC
- ambient temp.: -10°C ~ 55°C, humidity 30-95%
- medium temp: -20°C ~ 150°C
- pressure class: PN63, PN125, PN300
- connection to pipeline: thread, flange, welded, clamp

Accessories (upon request):

- 1) Heating
- 2) Two additional position switchers
- 3) Proportional regulation
- 4) Potentiometer – 5kΩ
- 5) Inbuilt LED position indicator
- 6) 12 VDC, 24 VDC, 24 VAC, 220-440 VAC (3-phases)

Model	MOMENT	90° rotation time	Current (230V AC)	Manual control	Weight	Flange ISO 5211
	[N.m]	[s]	[A]		[kg]	
JS-01	34	12	0.29	Páka	1.7	F03, F04, F05, F07
JS-02	49	12	0.4	Páka	1.8	F03, F04, F05, F07
JS-03	167	10	0.69	Páka	4.4	F05, F07
JS-03H	203	12	0,69	Kolo	7.9	F07, F10, F12
JS-04H	373	36	0.69	Kolo	8.6	F07, F10, F12
JS-05H	492	36	1.0	Kolo	8.8	F07, F10, F12
S-06H	598	36	1.1	Kolo	9.1	

